



Teak Flooring Product Specifications

This spec sheet is designed to give general information on our standard products. The below specifications are subject to change and limitation based on availability and other factors. Final specifications will be confirmed in writing by Indo Teak Design prior to any purchase.

Product Description

Indo Teak Design's reclaimed teak flooring has the rich color, tight grain, and legendary durability only found in centuries-old teak. Age and environment have seasoned this wood into an incredible swirl of muted Golds, coppers and tans, with rich brown and silver grain highlights. Plantation-grown teak cannot compare to Reclaimed Recycled Indonesian teak, in either looks or durability. Our reclaimed teak is graced with singular character from its previous life as vintage structures and defunct buildings in Indonesia. The reclamation of this old growth teak helps preserve standing teak forests and gives these amazing woods another lifetime of use and appreciation.

Source

Vintage buildings slated for demolition in Indonesia

Species

Tectona Grandis

Color Tones

Warm Honey to rich Golden Brown some muted Golds, Coppers and tans with rich brown and silver grain highlights.

Standard Dimensions

9/16" thick x 3-1/2" or 5-1/4" ,RL (2'-7') 3mm wear layer

Millwork

Tongue & groove, end-matched, MB4

Character

Prefilled nail and dowel holes, oxide stains, prefilled surface seasoning checks and occasional sound, tight knots.

Finish

Comes unfinished, unless otherwise specified.

Density/Hardness

Hardness rating of 1155.

Moisture Content

8-10%

Grading

100% FSC Certified recycled. Our flooring is graded for best face.

Packaging

Boxed and banded.

Lead Time

Typically ships within two to five working days. Call for availability.

Installation

Install according to National Wood Flooring Manufacturers Association (NOFMA) guidelines.

Certification

100% FSC-certified recycled

LEED

MR 4.1 & 4.2