



## **NATURAL ENGINEERED PATINA FLOORING**

### **Naturally Distressed Teak Flooring Specifications**

This spec sheet is designed to give general information on our standard products. The below specifications are subject to change and limitation based on availability and other factors. Final specifications will be confirmed in writing by Indo Teak Design prior to any purchase.

#### **Product Description**

Indo Teak Design's naturally Distressed Teak flooring is milled with the original surface face left intact, complete with nail holes, saw marks and other natural character. This product is not hand or faux distressed. It is naturally distressed from decades of tropical weathering and human use as part of vintage Indonesian structures slated for demolition . No two pieces are exactly alike. Each piece bears witness to its unique history and origins. The product adds instant character and personality to any project.

#### **Source**

Vintage and defunct buildings slated for demolition in Indonesia

#### **Species**

*Tectona grandis*

#### **Color Tones**

Rich tobacco browns with muted gold highlights and charcoal character marks.

#### **Standard Dimensions**

3/4" X 8" wide X 3mm wear layer, random solid lengths up to 2-7' long.

#### **Millwork**

Tongue & groove, Engineered 3 layered Reclaimed Teak on Teak, square-edge and end matched.

**Character**

Weathered surface face with nail holes, saw marks, oxide stains and other natural character.

**Finish**

Comes unfinished, unless otherwise specified.

**Density/Hardness**

Hardness rating of 1155.

**Moisture Content**

Kiln dried to eight to 10 percent moisture content.

**Packaging**

Banded.

**Grading**

100% FSC certified recycled teak flooring

**Lead Time**

Typically ships within 2 to 5 working days. Call for availability.

**Installation**

Install according to National Wood Flooring Manufacturers Association (NOFMA) guidelines.

**Certification**

FSC-certified recycled.

**LEED**

MR 4.1 & MR 4.2